

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



SC20 20A 600V TD Class G Fuse Bussmann Fuses

| - | |
|-----------------------------------|---|
| Catalog Number | SC20 |
| Manufacturer | Bussmann Fuses |
| Description | Eaton Bussmann Series Class G Fuse, SC, Fast-Acting, Current |
| | Limiting Fuse, 20 A, Rejection Style Fuse, Interrupting Rating Of |
| | 100 Ka At 600 Vac and 10 Ka At 170 VDC |
| Weight per unit | 0.0200 (lbs/each) |
| Product Category | Dual Element |
| eatures | |
| amperage rating | 20 Amp |
| class | G |
| connection | Ferrule End X Ferrule End |
| dimensions | 1.3750 IN X 0.3750 IN X 0.3750 IN |
| interrupt rating | 100000 Amp (RMS Symmetrical), 10000 Amp (DC) |
| media | Yes |
| Voltage Rating | 600 Vac, 170 Vdc |
| imensions and Weight | |
| Size | 0.41 In Diameter X 1.41 In Length |
| escriptions | |
| Description | 20A 600V TD CLASS G FUSE |
| extra long description | BUSS SC-20 BUSS SC FUSE CLASS G CLA |
| Features | Bussmann's SC type fuses are UL Class G and provide fast-acting |
| | (1/2-6 A) and time-delay (7-60 A) characteristics for circuit |
| | protection need. SC fuses are size rejecting in terms of their |
| | overall length thereby aiding in the prevention of overfusing |
| Long Description | Eaton Bussmann Series Class G fuse, SC, fast-acting, current |
| | limiting fuse, 20 A, rejection style fuse, interrupting rating of 100 |
| | kA at 600 Vac and 10 kA at 170 Vdc |
| Product Type | |
| Special Features | Rejection Style |
| lanufacturer Information | |
| Brand | COOPER BUSSMANN |
| GTIN | 00051712250207 |
| Manufacturers Part Number | SC-20 |
| UPC | 051712250207 |
| axonomies, Classifications, and C | Categories |
| | Fuses & Fuse Accessories |
| Туре | FUSE |



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging

standard

| Carton | 10 |
|--|--|
| Weight Per each | 0.02 |
| Uses, Certifications, and Standards Application | Ind Facilities & Factories - Facility: Safety and Security Systems |

RoHS Compliant, CE Marked