

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Catalog Number	SCR15GFSTSW
Manufacturer	Lutron
Description	Lutron Claro Tamper-Resistant Gfci Duplex Receptacle, 15-Amp, Snow
Weight per unit	0.3400 (lbs/each)
Product Category	Gen Purpose Recept & Surge Pro
eatures	
amperage rating	15
connection	Screw Terminal
insulation	Plastic
Number of Wires	3:4:5
Poles	2
Voltage Rating	125
Wattage	1875
Wire Size	10 to 14
aterial, Color, and Finish	
Color	SNOW
Finish	SATIN
mensions and Weight	
Size	4.69 x 2.94;119 x 75



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Descriptions	
Description	SATIN COLOR 15A RECEPTACLE SELF-TESTING GFCI SNOW
extra long description Features	LUT SCR-15-GFST-SW SC 15A GFCI SELF
reatures	Coordinate Lutron lighting controls and switches with Lutron Claro receptacles to complement your clients' decor. This
	self-testing GFCI receptacle automatically checks every 30
	seconds to see if critical components are damaged and GFCI
	protection is lost. There is an LED status indicator that provides
	peace of mind as well as a permanently installed internal
	tamper-resistant shutter mechanism, capable of resisting
	insertion of foreign elements into the receptacle openings. Install with screw terminals or
Long Description	Lutron Claro Tamper-Resistant GFCI Duplex Receptacle, 15-Amp,
	Snow
Product Type	SC 15A Gfci Self Testing Snow
Special Features	Self-testing technology allows GFCI to automatically check proper
	operation every 30 seconds. LEDs indicate status of GFCI
	protection function. Press reset button to reset GFCI after circuit interruption. Wallplate sold separately.
Manufacturer Information	
Brand	Lutron
GTIN	00784276159067
Manufacturers Part Number	SCR15GFSTSW
UPC	784276159067
Taxonomies, Classifications, and Cate	egories
Category Description	Residential receptacles
Туре	GFCI receptacle
Packaging	
Carton	1
Package	24
Weight Per each	0.34
Uses, Certifications, and Standards	
Application	Lighting Control
environmental conditions	0 to 90% humidity, non-condensing
Mounting	WALLBOX
nema rating	5-15R
standard	UL, CSA, NOM, NEC, CEC, OSHA