ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
Nacogdoches, TX 75964-0
Phone: 9365697941
Fax: 9365604685

SER201000 SER 2/0-2/0-2/0-1 ALU 1000'

KING WIRE INC.

Catalog Number	SER201000
Manufacturer	KING WIRE INC.
Description	Service Entrance Cable, Stranded, 12 Strands, 2/0 AWG Conductor Size, Aluminum Conductor Material, PVC Jacket Material, Polyethylene (XLPE) Insulation Material, 600 V, 115 A (60°C);135 A (75°C);150 A (90°C), Gray, 3 Conductors, 1000 ft Overall Length, 1264 mil Outside Diameter, +90 °C Operating Temperature, 653 lb/mft
Weight per unit	0.6330 (lbs/each)
Product Category	Aluminum-Ser /Ns-1/Ns-2

Features

Conductor Size	(3) 2/0 AWG
Current Rating	115 AMPERE (60 DEG C), 135 AMPERE (75 DEG C), 150 AMPERE (90 DEG C)
Ground Conductor Size	1 AWG
Ground Type	WITH GROUND WIRE
Stranding	12 STRANDS
Voltage Rating	600 V

Material, Color, and Finish

Jacket Material	GRAY PVC

Dimensions and Weight

Length	1000 ft
Outer Diameter	1264 MIL

ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
Nacogdoches, TX 75964-0
Phone: 9365697941
Fax: 9365604685

Descriptions

Additional Information	RoHS Compatible; Applicable Standard NEC/NFPA 70, Federal Specification A-A-59544
Commodity Description	ALUMINUM SE CABLE-SER / NS-1 / NS-2
Description	SER 2/0-2/0-2/0-1 ALU 1000'
Long Description	SER 2/0-2/0-2/0-1 AL SERVICE ENTRANCE CABLE, SER TYPE; 1000 FT; 1264 MIL OUTER DIAMETER; ALUMINUM CONDUCTOR MATERIAL; UL 44/83/854 APPROVAL; 600 V VOLTAGE RATING; 115 AMPERE (60 DEG C), 135 AMPERE (75 DEG C), 150 AMPERE (90 DEG C) CURRENT RATING; 90 DEG C TEMPERATURE RATING
Extra Long Description	SER TYPE; 1000 FT; 1264 MIL OUTER DIAMETER; ALUMINUM CONDUCTOR MATERIAL; UL 44/83/854 APPROVAL; 600 V VOLTAGE RATING; 115 AMPERE (60 DEG C), 135 AMPERE (75 DEG C), 150 AMPERE (90 DEG C) CURRENT RATING; 90 DEG C TEMPERATURE RATING; WITH GROUND WIRE; (3) 2/0 AWG CONDUCTOR SIZE; GRAY PVC JACKET MATERIAL; REEL PACKAGE TYPE; 12 STRANDS STRANDING; 1 AWG GROUND CONDUCTOR SIZE; ALUMAFLEX[R] BRAND; ROHS COMPATIBLE; APPLICABLE STANDARD NEC/NFPA 70, FEDERAL SPECIFICATION A-A-59544; SE MODEL

Manufacturer Information

Brand	Southwire AlumaFlex[R]
GTIN	00032886584862
Model	SE
UPC	803940

Taxonomies, Classifications, and Categories

Category Description	SERVICE ENTRANCE - SEU & SER
Type	SER

Availability

Status	Inactive
Minimum Qty	1000

Packaging

Carton	1000
Package Type	Reel
Weight Per Each	0.6330 (lbs/each)

Uses, Certifications, and Standards

Approval	UL 44/83/854
Temperature Rating	90 DEG C