

SADDLEGRIP® Connectors



For aluminum and steel Flex • AC • AC90 • MCI • MCI-A cable • HCF steel and aluminum cable.
Zinc die-cast.

| CATALOG NUMBER | UPC/DCI/NAED MFG #018997 | TRADE SIZE | KO SIZE | UNIT PKG | STD PKG | DIM A | DIM B | DIM C | CABLE RANGE | END STOP DIAMETER |
|----------------|--------------------------|------------|---------|----------|---------|-------|-------|-------|-------------|-------------------|
| SG38‡ | 18065 | 3/8 | 1/2 | 50 | 500 | 1.000 | .400 | 1.077 | .405-.612 | .400 |
| SG38A*‡ | 80138 | 3/8 | 1/2 | 50 | 500 | 1.090 | .490 | 1.077 | .405-.612 | .400 |
| SG380‡ | 18060 | 3/8 | 1/2 | 50 | 500 | 1.000 | .400 | 1.077 | .405-.612 | .400 x .580 |
| SG380A*‡ | 80140 | 3/8 | 1/2 | 50 | 500 | 1.090 | .490 | 1.077 | .405-.612 | .400 x .580 |
| SG40‡ | 01740 | 7/16 | 1/2 | 50 | 500 | 1.480 | .480 | 1.125 | .530-.790 | .620 |
| SG50‡ | 07500 | 1/2 | 1/2 | 50 | 500 | 1.480 | .480 | 1.277 | .710-.910 | .620 |
| SG50A*‡ | 37501 | 1/2 | 1/2 | 50 | 500 | 1.511 | .511 | 1.277 | .710-.910 | .620 |
| SG75 | 18075 | 3/4 | 3/4 | 20 | 200 | 1.435 | .450 | 1.470 | .840-1.110 | .820 |
| SG75A* | 17751 | 3/4 | 3/4 | 20 | 200 | 1.466 | .481 | 1.470 | .840-1.110 | .820 |

*Provided with insulated throat.

‡Also for MCI-A cable. See page E-30 and E-31 for MCI-A cable ranges.

For cables smaller than 0.405" see L16 on page E-13 and L16ST on page E-5.

Refer to chart on page E-28 for a list of cable types.


Concrete tight when taped.



SG380



SG38



SADDLEGRIP® Connectors



For aluminum and steel Flex • AC • AC90 • MCI • MCI-A cable • HCF steel and aluminum cable.
Zinc die-cast.

| CATALOG NUMBER | UPC/DCI/NAED MFG #018997 | TRADE SIZE | KO SIZE | UNIT PKG | STD PKG | DIM A | DIM B | DIM C | CABLE RANGE | END STOP DIAMETER |
|----------------|--------------------------|------------|---------|----------|---------|-------|-------|-------|-------------|-------------------|
| SG38‡ | 18065 | 3/8 | 1/2 | 50 | 500 | 1.000 | .400 | 1.077 | .405-.612 | .400 |
| SG38A*‡ | 80138 | 3/8 | 1/2 | 50 | 500 | 1.090 | .490 | 1.077 | .405-.612 | .400 |
| SG380‡ | 18060 | 3/8 | 1/2 | 50 | 500 | 1.000 | .400 | 1.077 | .405-.612 | .400 x .580 |
| SG380A*‡ | 80140 | 3/8 | 1/2 | 50 | 500 | 1.090 | .490 | 1.077 | .405-.612 | .400 x .580 |
| SG40‡ | 01740 | 7/16 | 1/2 | 50 | 500 | 1.480 | .480 | 1.125 | .530-.790 | .620 |
| SG50‡ | 07500 | 1/2 | 1/2 | 50 | 500 | 1.480 | .480 | 1.277 | .710-.910 | .620 |
| SG50A*‡ | 37501 | 1/2 | 1/2 | 50 | 500 | 1.511 | .511 | 1.277 | .710-.910 | .620 |
| SG75 | 18075 | 3/4 | 3/4 | 20 | 200 | 1.435 | .450 | 1.470 | .840-1.110 | .820 |
| SG75A* | 17751 | 3/4 | 3/4 | 20 | 200 | 1.466 | .481 | 1.470 | .840-1.110 | .820 |

*Provided with insulated throat.

‡Also for MCI-A cable. See page E-30 and E-31 for MCI-A cable ranges.

For cables smaller than 0.405" see L16 on page E-13 and L16ST on page E-5.

Refer to chart on page E-28 for a list of cable types.

Concrete tight when taped.



SG380



SG38

