## Kellems® Wire Management Products Straight Male Cord Connectors **Cord Connectors**

# HUBBELL

### **Features**

- Aluminum cord connector provides durable performance
- Knurled finish makes them easy to handle and maintain UL listing by hand tighteningUL listing by hand tightening
- Lightweight design

**Ordering Information** 

Description Cord Connectors, Straight Male, Aluminum

Color Code Yellow

**UPC** 783585200378

Catalog Number SHC1037

Listings

**UL** Listed **CSA Certified** 

**Specifications** 

Material Form Size F3 3/4 Inch NPT Hub Size

Cord Diameter Range

Inches (mm)

Aluminum

.63"-.75" (15.9-19.0)

**Performance** 

**Environmental** 

Used in hazardous locations per Class I Div. 2, Class II Hazardous Locations

Div. 1 & 2, Class III Div. 1 & 2 in accordance with the NEC

**Operating Temperatures** -30°F to +225°F (-34°C to +107°C)



**Online Resources** 

eCatalog



## Kellems® Wire Management Products Straight Male Cord Connectors **Cord Connectors**

# HUBBELL

### **Features**

- Aluminum cord connector provides durable performance
- Knurled finish makes them easy to handle and maintain UL listing by hand tighteningUL listing by hand tightening
- Lightweight design

**Ordering Information** 

Description Cord Connectors, Straight Male, Aluminum

Color Code Yellow

**UPC** 783585200378

Catalog Number SHC1037

Listings

**UL** Listed **CSA Certified** 

**Specifications** 

Material Form Size F3 3/4 Inch NPT Hub Size

Cord Diameter Range

Inches (mm)

Aluminum

.63"-.75" (15.9-19.0)

**Performance** 

**Environmental** 

Used in hazardous locations per Class I Div. 2, Class II Hazardous Locations

Div. 1 & 2, Class III Div. 1 & 2 in accordance with the NEC

**Operating Temperatures** -30°F to +225°F (-34°C to +107°C)



**Online Resources** 

eCatalog

