

Kellems® Wire Management Products  
Straight Male Cord Connectors  
Cord Connectors

# HUBBELL

## Features

- Aluminum cord connector provides durable performance

## Ordering Information

Description	Color Code	UPC	Catalog Number
Cord Connectors, Straight Male, Aluminum	Yellow	783585200415	SHC1041



## Listings

UL Listed  
CSA Certified

## Online Resources

[eCatalog](#)

## Specifications

Material	Aluminum
Form Size	F4
NPT Hub Size	1 Inch
Cord Diameter Range Inches (mm)	.63"-.75" (15.9-19.0)

## Performance

### Environmental

Hazardous Locations Used in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 in accordance with the NEC

Operating Temperatures -30°F to +225°F (-34°C to +107°C)

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.



Kellems® Wire Management Products  
Straight Male Cord Connectors  
Cord Connectors

# HUBBELL

## Features

- Aluminum cord connector provides durable performance

## Ordering Information

Description	Color Code	UPC	Catalog Number
Cord Connectors, Straight Male, Aluminum	Yellow	783585200415	SHC1041



## Listings

UL Listed  
CSA Certified

## Online Resources

[eCatalog](#)

## Specifications

Material	Aluminum
Form Size	F4
NPT Hub Size	1 Inch
Cord Diameter Range Inches (mm)	.63"-.75" (15.9-19.0)

## Performance

### Environmental

Hazardous Locations Used in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 in accordance with the NEC

Operating Temperatures -30°F to +225°F (-34°C to +107°C)

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

