



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## ST3 1" Myers Hub *Crouse-Hinds*

|                  |   |
|------------------|---|
| Catalog Number   | ST3   |
| Manufacturer     | Crouse-Hinds  |
| Description      | Hub, ST Model, Straight, Natural, Insulated, Threaded<br>Connection, 1 In Hub Size, 0.4 LB/Ea |
| Weight per unit  | 0.4000 (lbs/each)   |
| Product Category | Rigid Conduit Fittings - Steel  |

### Features

|            |                                   |
|------------|-----------------------------------|
| connection | Threaded                          |
| dimensions | 1.7200 IN X 1.9900 IN X 1.7200 IN |
| Material   | Zinc                              |

### Material, Color, and Finish

|        |                      |
|--------|----------------------|
| Finish | NICKEL CHROME PLATED |
|--------|----------------------|

### Dimensions and Weight

|      |      |
|------|------|
| Size | 1 in |
|------|------|

### Descriptions

|                        |                                    |
|------------------------|------------------------------------|
| Description            | 1" MYERS HUB                       |
| extra long description | MYERS ST 3 CH MYERS 1 ZINC CONDUIT |

### Manufacturer Information

|       |                |
|-------|----------------|
| Brand | Eaton          |
| GTIN  | 00784731100054 |
| UPC   | 784731100054   |

### Taxonomies, Classifications, and Categories

|                      |   |
|----------------------|---|
| Category Description | Watertight Hub, 3-PIECE COUPLINGS, THREADLESS COUPLINGS<br>AND THREADLESS CONNECTOR |
| Type                 | Basic hub   |

### Packaging

|                 |     |
|-----------------|-----|
| Carton          | 25  |
| Weight Per each | 0.4 |

### Uses, Certifications, and Standards

|                       |  |
|-----------------------|--|
| Enclosure<br>standard | NEMA 2/3/3R/4/4X/12<br>UL 514B, CUL, CSA C22.2 |
|-----------------------|--|