



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



SWB2 KLRK SWB-2 3/4 Expl-PRF Box

Hubbell--Killark

| | |
|------------------|---|
| Catalog Number | SWB2 |
| Manufacturer | Hubbell--Killark |
| Description | SWB Series - Aluminum Dead-End Single-Gang Device Body For Use With XCS/XS/XT Cover Assemblies - Hub Size 3/4 Inch - 5-7/8 Inch X 3 Inch X 2-1/4 Inch |
| Weight per unit | 1.4 (lbs/each) |
| Product Category | Junction, Surface, & Back Boxes |

Dimensions and Weight

| | |
|------|----------------------------|
| Size | 7.875 in x 3.5 in x 3.5 in |
|------|----------------------------|

Descriptions

| | |
|------------------------|--|
| Description | KLRK SWB-2 3/4 EXPL-PRF BOX |
| extra long description | KLRK SWB-2 3/4" 5 7/8X3X2 1/4 SWB B |
| Long Description | SWB Series - Aluminum Dead-End Single-Gang Device Body For Use With XCS/XS/XT Cover Assemblies - Hub Size 3/4 Inch - 5-7/8 Inch X 3 Inch X 2-1/4 Inch |
| Product Type | 3/4" 5 7/8X3X2 1/4 SWB Body |
| Special Features | Killark SWB SERIES CONTROL STATION BACK BOXES provide control solutions in hazardous location areas to supply;START/STOP Motor Functions, LED Pilot Light Indications and more for use with Killark XCS and XS Cover Assemblies. For use in Class 1 Division 1 & 2, Class 1 Zone 1 & 2 areas for indoor use and are Non-Factory Sealed requiring the need for a conduit seal fitting. UL Listed and CSA Certified. The SWB is offered in a wide variety of configurations from 1/2" to 1" dead end and feed through for single |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | KILLARK |
| GTIN | 00783936630021 |
| Manufacturers Part Number | SWB-2 |
| series | SWB |
| UPC | 783936630021 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|--|
| Category Description | Datacom Wiring Devices and Accessories |
| Type | Aluminum device body |

Packaging

| | |
|-----------------|------|
| Carton | 1 |
| Weight Per each | 1.39 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Application

Hazardous locations due to the presence of flammable gases or vapors, combustible dusts, or easily ignitable fiber or flyings. Installations at petroleum refineries, chemical and petrochemical plants, and other processing or storage facilities where similar hazards exist. Use in conjunction with magnetic starters or contactors for remote control of motors.

Enclosure

Aluminum enclosure

environmental conditions

Hazardous locations

Mounting

WALL

standard

UL, CSA