



120 X 240 - 12/24  
120 X 240 Primary Volts - 12/24 Secondary Volts - 1Ø  
Buck-Boost Transformer - Single Phase

1082



Catalog #: T181049

**PRODUCT FEATURES**

- UL listed, CSA certified
- UL Type 3R epoxy encapsulated
- Single or Three Phase Applications
- Wall Mounted
- Covered under Acme's 10 year limited warranty

**BENEFITS**

- Easily configured for numerous applications
- Lower cost solution
- 5-10 times increase in KVA

**UL STANDARD**

UL 506

**CSA STANDARD**

C22.2 No 47

**WARRANTY**

Acme Electric Warranty Card  
[www.hubbell-acmeElectric.com/Images/news/Acme\\_Warranty.pdf](http://www.hubbell-acmeElectric.com/Images/news/Acme_Warranty.pdf)

**GENERAL PRODUCT INFORMATION**

|                       |           |
|-----------------------|-----------|
| VA:                   | 150       |
| kVA:                  | -         |
| Primary Voltage:      | 120 X 240 |
| Secondary Voltage:    | 12/24     |
| Frequency:            | 50/60 Hz  |
| Max Temperature Rise: | 115°C     |
| UL Insulation Class:  | 180°C     |

**PRODUCT MEASUREMENTS**

|                  |             |
|------------------|-------------|
| Height (In./cm): | 7.16 (18.2) |
| Width (In./cm):  | 3.89 (9.9)  |
| Depth (In./cm):  | 3.67 (9.3)  |

**CONFIGURATION**

|                    |              |
|--------------------|--------------|
| Construction Type: | Encapsulated |
| Mounting Type:     | Wall         |

**PACKAGING**

|                       |         |
|-----------------------|---------|
| Ship Weight (Lbs/Kg): | 7 (3.2) |
|-----------------------|---------|

**COMPLIANCES**

UL Standard: UL 506  
UL Listed: File E79947  
CSA Standard: C22.2 No 47  
CSA Listed: LR7357-26  
Warranty: Acme Electric Warranty Card  
[www.hubbell-acmeElectric.com/Images/news/Acme\\_Warranty.pdf](http://www.hubbell-acmeElectric.com/Images/news/Acme_Warranty.pdf)



120 X 240 - 12/24  
120 X 240 Primary Volts - 12/24 Secondary Volts - 1Ø  
Buck-Boost Transformer - Single Phase

1082



Catalog #: T181049

**PRODUCT FEATURES**

- UL listed, CSA certified
- UL Type 3R epoxy encapsulated
- Single or Three Phase Applications
- Wall Mounted
- Covered under Acme's 10 year limited warranty

**BENEFITS**

- Easily configured for numerous applications
- Lower cost solution
- 5-10 times increase in KVA

**UL STANDARD**

UL 506

**CSA STANDARD**

C22.2 No 47

**WARRANTY**

Acme Electric Warranty Card  
[www.hubbell-acmeElectric.com/Images/news/Acme\\_Warranty.pdf](http://www.hubbell-acmeElectric.com/Images/news/Acme_Warranty.pdf)

**GENERAL PRODUCT INFORMATION**

|                       |           |
|-----------------------|-----------|
| VA:                   | 150       |
| kVA:                  | -         |
| Primary Voltage:      | 120 X 240 |
| Secondary Voltage:    | 12/24     |
| Frequency:            | 50/60 Hz  |
| Max Temperature Rise: | 115°C     |
| UL Insulation Class:  | 180°C     |

**PRODUCT MEASUREMENTS**

|                  |             |
|------------------|-------------|
| Height (In./cm): | 7.16 (18.2) |
| Width (In./cm):  | 3.89 (9.9)  |
| Depth (In./cm):  | 3.67 (9.3)  |

**CONFIGURATION**

|                    |              |
|--------------------|--------------|
| Construction Type: | Encapsulated |
| Mounting Type:     | Wall         |

**PACKAGING**

|                       |         |
|-----------------------|---------|
| Ship Weight (Lbs/Kg): | 7 (3.2) |
|-----------------------|---------|

**COMPLIANCES**

UL Standard: UL 506  
UL Listed: File E79947  
CSA Standard: C22.2 No 47  
CSA Listed: LR7357-26  
Warranty: Acme Electric Warranty Card  
[www.hubbell-acmeElectric.com/Images/news/Acme\\_Warranty.pdf](http://www.hubbell-acmeElectric.com/Images/news/Acme_Warranty.pdf)