



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## TCF30RN 30A Non-Inp Cube Fuse

*Bussmann Fuses*

Catalog Number	TCF30RN
Manufacturer	Bussmann Fuses
Description	Eaton Bussmann Series TCF Fuse, 30 A, 60 HZ, 50 HZ, Dual, CF, Black, Blade End, Time Delay, Class CF, 10 Sec At 500%, 300 Kaic At 600 V, 100 Kaic At 300 VDC, Glass Filled Pes, 35 MM Din Rail, Chassis, 600 V, 300 VDC
Weight per unit	0.1000 (lbs/each)
Product Category	Tools & Testers

### Features

amperage rating	30 A
class	Class CF
connection	Blade End
dimensions	1.8800 IN X 0.7500 IN X 1.7500 IN
element	Dual
interrupt rating	300 kAIC at 600 Vac 100 kAIC at 300 Vdc
Material	Glass Filled PES
media	Yes
Response Time	10 S at 500%
Voltage Rating	600 Vac, 300 Vdc

### Descriptions

Description	30A NON-INP CUBE FUSE
extra long description	BUSS TCF30RN CUBEFUSE, TCF 30A NON-
Features	The revolutionary Bussmann™ series Low-Peak™ CUBEFuse™ delivers the smallest footprint compared to any Class CC, J or RK fuse solution — requiring up to 70 less space when combined with its unique fuse holder or UL 98 Listed Compact Circuit Protector switch. Freeing up space is powerful. And the CUBEFuse does just that, while packing up to a 300 kA interrupting rating and enabling higher equipment short-circuit current rating (SCCR). Available from 1 to 400 amps.
Long Description	Eaton Bussmann series TCF fuse, 30 A, 60 Hz, 50 Hz, Dual, CF, Black, Blade end, Time delay, Class CF, 10 sec at 500%, 300 kAIC at 600 V, 100 kAIC at 300 Vdc, Glass filled PES, 35 mm DIN rail, Chassis, 600 V, 300 Vdc
Product Type	Cubefuse, TCF 30A Non-Ind
Special Features	Finger Safe



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Manufacturer Information

Brand	Eaton
GTIN	00051712220965
Manufacturers Part Number	TCF30RN
UPC	051712220965

## Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	FUSE

## Packaging

Carton	1
Package	12
Weight Per each	0.1

## Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Safety and Security SystemsDatacenters - Facilities: Power DistributionCommercial / Institutional Buildings / Structures - Critical PowerInd Facilities & Factories - Facility: Power Distribution and ControlStationary Machinery and Equipment Outside Factory - HVAC
Mounting standard	35 mm DIN Rail, Chassis CSA Certified,UL Listed,CE Marked,RoHS Compliant