



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## TCF6 6A Finger Safe Fuse

*Bussmann Fuses*

Catalog Number	TCF6
Manufacturer	Bussmann Fuses
Description	6A 600V Special Purpose Cubefuse Fuse, Dual Element Time Delay
Weight per unit	0.1000 (lbs/each)
Product Category	Tools & Testers

### Features

amperage rating	6 A
class	Class CF
connection	Blade End
dimensions	1.8800 IN X 0.7500 IN X 1.7500 IN
element	Dual
interrupt rating	300 kAIC at 600 Vac100 kAIC at 300 Vdc
Material	Glass Filled PES
media	Yes
Response Time	10 S at 500%
Voltage Rating	600 Vac, 300 Vdc

### Descriptions

Description	6A FINGER SAFE FUSE
extra long description	EFSE TCF6 6A FUSE ASSY
Features	The revolutionary Bussmann <sup>TM</sup> series Low-Peak <sup>TM</sup> CUBEFuse <sup>TM</sup> delivers the smallest footprint compared to any Class CC, J or RK fuse solution — requiring up to 70 less space when combined with its unique fuse holder or UL 98 Listed Compact Circuit Protector switch. Freeing up space is powerful. And the CUBEFuse does just that, while packing up to a 300 kA interrupting rating and enabling higher equipment short-circuit current rating (SCCR). Available from 1 to 400 amps.
Long Description	6A 600V Special Purpose CUBEFUSE Fuse, Dual Element Time Delay
Product Type	6A Fuse Assy
Special Features	Finger Safe

### Manufacturer Information

Brand	Eaton Bussmann series
GTIN	00051712614979
Manufacturers Part Number	TCF6
UPC	051712614979



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Taxonomies, Classifications, and Categories

Category Description.....Fuses & Fuse Accessories

Type.....FUSE

## Packaging

Carton.....12

Weight Per each.....0.1

## Uses, Certifications, and Standards

Application.....Ind Facilities & Factories - Facility: Safety and Security  
.....SystemsDatacenters - Facilities: Power DistributionCommercial /  
.....Institutional Buildings / Structures - Critical PowerInd Facilities &  
.....Factories - Facility: Power Distribution and ControlStationary  
.....Machinery and Equipment Outside Factory - HVAC

Mounting.....35 mm DIN Rail, Chassis

standard.....UL Listed,CSA Certified,CE Marked,RoHS Compliant