



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## TF4224 Therm O/L Relay 20.0-24.0a

*Industrial Connections &*

|                  |  |
|------------------|--|
| Catalog Number   | TF4224   |
| Manufacturer     | Industrial Connections &                                   |
| Description      | 3 Pole Thermal Overload Relay With 20-24 Amp Setting Range |
| Weight per unit  | 0.3650 (lbs/each)  |
| Product Category | Overload Relays & Accessories                              |

### Features

|       |      |
|-------|------|
| Poles | 3 in |
|-------|------|

### Dimensions and Weight

|      |                       |
|------|-----------------------|
| Size | 3.48x1.77x2.78 Inches |
|------|-----------------------|

### Descriptions

|                        |  |
|------------------------|--|
| Description            | THERM O/L RELAY 20.0-24.0A                                 |
| extra long description | ABB TF42-24 THERMAL O/L RELAY, 20.0                        |
| Long Description       | 3 pole thermal overload relay with 20-24 amp setting range |
| Product Type           | Relais De Surcharge Thermique                              |
| Special Features       | Economic overload protection                               |

### Manufacturer Information

|                           |                |
|---------------------------|----------------|
| Brand                     | ABB            |
| GTIN                      | 00804325558587 |
| Manufacturers Part Number | TF42-24        |
| UPC                       | 804325558587   |

### Taxonomies, Classifications, and Categories

|                      |                      |
|----------------------|----------------------|
| Category Description | PHASE FAILURE RELAYS |
| Type                 | THERMAL              |

### Packaging

|                 |       |
|-----------------|-------|
| Carton          | 1     |
| Weight Per each | 0.365 |

### Uses, Certifications, and Standards

|             |   |
|-------------|---|
| Application | Offers reliable protection for motors in the event of overload or phase failure |
| standard    | UL, CSA, CE   |