

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



TM873BK Radiant Switch 3W 15A 120/277V BK

Pass & Seymour/Legrand

Catalog Number	TM873BK
Manufacturer	Pass & Seymour/Legrand
Description	Allowing Control Of A Light or Fixture From Two Separately Located Switches, The Radiant Registered 3-Way Switch Upgrades Your Space With Clean Lines and Smooth Paddle Action For A Sophisticated Touch. Made Exclusively For Use With Screwless Wall Plates From The Radiant Registered Collection, Sold Separately.
Weight per unit	0.1506 (lbs/each)
Product Category	Gen Purpose Switches
Features	
Contact Rating	15 Amp, 120/125 VAC
gang	1
insulation	Bare
Material	Thermoplastic
media	Yes
Mounting Type	Box
Number of Gangs	1.0
Number of Switches	1.0
orientation	Vertical
Poles	1, 3-Way
Switch Type	Paddle
Voltage	120/277 V
Wire Size	#14 - #10 Awg
Material, Color, and Finish	
Finish	Matte
Dimensions and Weight	
Size	6.25"
Thickness	2"



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

ions
OH 13

- Description	RADIANT SWITCH 3W 15A 120/277V BK
extra long description	P&S TM873BK RADIANT SWITCH 3W 15A 1
Long Description	Allowing control of a light or fixture from two separately located switches, the radiant Registered 3-Way Switch upgrades your space with clean lines and smooth paddle action for a sophisticated touch. Made exclusively for use with screwless Wall Plates from the radiant Registered Collection, sold separately.
Product Type	Radiant Switch 3W 15A 120/277V BK
Special Features	Designer style satin finish rocker, push wire 14awg, narrow back body
nufacturar Information	•

Manufacturer Information

Brand	Pass and Seymour	
GTIN	00785007245424	
Manufacturers Part Number	TM873-BK	
UPC	785007245424	

Taxonomies, Classifications, and Categories

Category Description	Residential Switches
Туре	SWITCH

Trade Size

Amperage	15.0

Packaging

Carton	10
Package	100
Weight Per each	0.1506

Uses, Certifications, and Standards

Application	Residential/Commercial
Mounting	WALL
standard	CULUS, UL, UL 20