# Eaton TMR5Y05120

# Catalog Number: TMR5Y05120

TMR5 Series Time Delay Relays, Octal style terminals, 8 pins, Repeat cycle (ON time first followed up off time and repeating), 0.1-10 sec time delay, 120 Vac/dc input voltage, 10A max. allowable load, DPDT contact configuration

## General specifications



Eaton timing relay

**UPC** 

786685124926

**Product Height** 

2.4 in

**Product Weight** 

0.3 lb

Catalog Number

TMR5Y05120

Product Length/Depth

3.5 in

**Product Width** 

1.7 in

Warranty

Eaton Selling Policy 25-000, one (1) year

from the date of installation of the

Product or eighteen (18) months from the

date of shipment of the Product,

whichever occurs first.

Compliances Certifications

CE Marked UL Listed (when used with Eaton socket)

cRUus

### Catalog Notes

**RoHS Compliant** 

Fixed time delay settings are available for orders of 50 pieces or more. Contact EatonCare for additional information at 877-ETN-CARE (386-2273). Dual knob unit with independently selectable/adjustable ON/OFF times.





### defaultTaxonomyAttributeLabel

Type

Timing relay

**Prod load** 

10A

Number of pins

8

Operating mode

Repeat cycle (ON time first followed up off time and repeating)

Contact configuration

DPDT

Series

TMR5

Dielectric strength

2000 V between poles

Input voltage

120 Vac/dc

**Terminals** 

Octal

Time delay

0.1-10 seconds

### Resources

Eaton's Volume 7—Logic Control, Operator Interface and Connectivity

### Installation instructions

TMR5 series non-programmable plug-in time delay relays

### Specifications and datasheets

Eaton Specification Sheet - TMR5Y05120



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



# Eaton TMR5Y05120

# Catalog Number: TMR5Y05120

TMR5 Series Time Delay Relays, Octal style terminals, 8 pins, Repeat cycle (ON time first followed up off time and repeating), 0.1-10 sec time delay, 120 Vac/dc input voltage, 10A max. allowable load, DPDT contact configuration

## General specifications



Eaton timing relay

**UPC** 

786685124926

**Product Height** 

2.4 in

**Product Weight** 

0.3 lb

Catalog Number

TMR5Y05120

Product Length/Depth

3.5 in

**Product Width** 

1.7 in

Warranty

Eaton Selling Policy 25-000, one (1) year

from the date of installation of the

Product or eighteen (18) months from the

date of shipment of the Product,

whichever occurs first.

Compliances Certifications

CE Marked UL Listed (when used with Eaton socket)

cRUus

### Catalog Notes

**RoHS Compliant** 

Fixed time delay settings are available for orders of 50 pieces or more. Contact EatonCare for additional information at 877-ETN-CARE (386-2273). Dual knob unit with independently selectable/adjustable ON/OFF times.





### defaultTaxonomyAttributeLabel

Type

Timing relay

**Prod load** 

10A

Number of pins

8

Operating mode

Repeat cycle (ON time first followed up off time and repeating)

Contact configuration

DPDT

Series

TMR5

Dielectric strength

2000 V between poles

Input voltage

120 Vac/dc

**Terminals** 

Octal

Time delay

0.1-10 seconds

### Resources

Eaton's Volume 7—Logic Control, Operator Interface and Connectivity

### Installation instructions

TMR5 series non-programmable plug-in time delay relays

### Specifications and datasheets

Eaton Specification Sheet - TMR5Y05120



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.

