

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



TR90R 250V RK5 TD Fuse Mersen Fuses

Catalog Number	TR90R
Manufacturer	Mersen Fuses
Description	Fuse TR-R - Class RK5 - Time-Delay 250VAC 250VDC 90A Blade Tri-Onic®
Weight per unit	0.3500 (lbs/each)
Product Category	Current Limiting
Features	
AC Voltage Rating	250
amperage rating	90
class	Class RK5
connection	Blade
interrupt rating	200
Voltage Rating	250
Material, Color, and Finish	
Body Material	PolyTube
Dimensions and Weight	
Size	5.88 x 0.06



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Descriptions	250V RK5 TD FUSE
Description extra long description	Mersen TR90R Fuse TR-R - Class RK5
Features	Tri-Onic TR-R current-limiting time-delay fuses are engineered for overcurrent protection of motors, transformers, service entrance equipment, feeders and branch-circuits. The time-delay characteristics of the TR-R safely handle harmless starting currents and inrush currents associated with today's motors and transformers.
Long Description	Fuse TR-R - Class RK5 - Time-Delay 250VAC 250VDC 90A Blade Tri-Onic®
Product Type Short Description	Fuse TR-R - Class RK5 - Time-Delay 250VAC 250VDC 90A Blade 250V 90A 5 7/8x1 1/16 RK5
Special Features	Time-delay Current-limiting AC & DC rated Optional solid state SmartSpot blown fuse indicator Time-delay for motor start-ups and transformer inrush currents without nuisance opening Current-limiting for low peak let-thru current Rejection-style design prevents replacement errors (when used with recommended fuse blocks) Easy-to-read label for quick brand recognition and replacement Metal-embossed date and catalog number for traceability and lasting identification Fiberglass body provides dimensional stabili
Manufacturer Information	
Brand	Mersen
GTIN	00782001748005
Manufacturers Part Number	TR90R
UPC	782001748005
Taxonomies, Classifications, and Cate	
Туре	CLASS RK5
Packaging	
Carton	1
Weight Per each	0.35
Uses, Certifications, and Standards	
Application	Motor circuits Mains Feeders Branch circuits Transformers Service entrance equipment General-purpose equipment
Mounting	Clip
standard	UL listed to standard 248-12 File E2137 CSA certified to standard C22.2 no. 248.12 DC listed to UL standard 248 TRS only