




ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



TSC05 Seal Compound .5oz *Crouse-Hinds*

Catalog Number	TSC05
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series TSC Epoxy Sealing Compound, 0.5 Oz Tube, Quantity Of 10
Weight per unit	0.8200 (lbs/each)
Product Category	Paint, Chemicals, Etc.

Features

dimensions	5.0000 IN X 1.0000 IN X 1.0000 IN
Form	Putty
Material	Epoxy
specific gravity	1.894140
Temperature Range	90 Deg F (Storage)

Material, Color, and Finish

Color	Green
-------	-------

Dimensions and Weight

Size	0.5 Oz
------	--------

Descriptions

Description	SEAL COMPOUND .5OZ
extra long description	CRS-H TSC05 10 0.5OZ TUBE TSC EPOXY
Features	ES explosionproof sealing hubs from Eaton Crouse-Hinds Division are used to seal vertical conduit risers at switchgear and motor control centers, sheet metal structures or cast boxes and enclosures. When used with TSC sealing compound, ES hubs can seal horizontal conduit runs at enclosures. TSC epoxy sealing compound is a two-part epoxy sealing compound that may be used to seal ES sealing hubs. It is quick and easy to measure, mix and install. The compound is kneaded until a uniform color is obtained.
Long Description	Eaton Crouse-Hinds series TSC epoxy sealing compound, 0.5 oz tube, quantity of 10
Product Type	10 0.5OZ Tube TSC Epoxy Sealing Compound
Special Features	Explosionproof, Watertight

Manufacturer Information

Brand	Eaton
GTIN	00782274886558
Manufacturers Part Number	TSC05
UPC	782274886558



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	ADHESIVES
Type	Epoxy sealing compound

Packaging

Carton	1
Package	10
Weight Per each	0.82

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
standard	UL 886, CSA C22.2