



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



TY26MX 11.08" Ty-Rap (Bulk)

Abb Installation Products, Inc

Catalog Number	TY26MX
Manufacturer	Abb Installation Products, Inc
Description	Cable Tie, Black Polyamide (Nylon 6.6) For Temperatures Up to , Weather and Ultra-Violet Resistant For Indoor and Outdoor Applications, , Length Of 284.4MM (11.10 Inches), Width Of 3.56MM (0.14 Inches), , Tensile Strength Rating Of 133.4 Newtons (30 Pounds), Temperature Up to 85 Degress Celsius (185 F)Bulk Pack
Weight per unit	0.0030 (lbs/each)
Product Category	Cable Ties & Wraps

Features

Tensile Strength	40:180
------------------	--------

Dimensions and Weight

Length	10.9
Thickness	0.04
Width	0.14

Descriptions

Description	11.08" TY-RAP (BULK)
extra long description	ABB TY26MX CABLE TIE 30LB 11.10IN U
Long Description	Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to , Weather and Ultra-Violet Resistant for Indoor and Outdoor Applications, , Length of 284.4mm (11.10 Inches), Width of 3.56mm (0.14 Inches), , Tensile Strength Rating of 133.4 Newtons (30 pounds), Temperature up to 85 degress celsius (185 F)Bulk Pack
Product Type	Cable Tie 30LB 11.10IN Uv Black Nyl
Special Features	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time

Manufacturer Information

Brand	Ty-Rap
GTIN	00786210839875
Manufacturers Part Number	TY26MX
UPC	786210839875

Taxonomies, Classifications, and Categories

Category Description	Screws, Bolts, Staples, Jack Chains, Washers & TY-Raps
Type	HIGH PERFORMANCE



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Availability

minimum qty 1000

Packaging

Carton 1000

Package 10000

Weight Per each 0.003

Uses, Certifications, and Standards

standard UL E49405