

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

TY26MX 11.08" Ty-Rap (Bulk) Abb Installation Products, Inc	
Catalog Number	TY26MX
Manufacturer	Abb Installation Products, Inc
Description	Cable Tie, Black Polyamide (Nylon 6.6) For Temperatures Up to , Weather and Ultra-Violet Resistant For Indoor and Outdoor Applications, , Length Of 284.4MM (11.10 Inches), Width Of 3.56MM (0.14 Inches), , Tensile Strength Rating Of 133.4 Newtons (30 Pounds), Temperature Up to 85 Degress Celsius (185 F)Bulk Pack
Weight per unit	0.0030 (lbs/each)
Product Category	Cable Ties & Wraps
Features	
Tensile Strength	40
Dimensions and Weight	
Length	10.9
Thickness	0.04
Width	0.14
Descriptions	
Description	11.08" TY-RAP (BULK)
extra long description	ABB TY26MX CABLE TIE 30LB 11.10IN U
Long Description	Cable Tie, Black Polyamide (Nylon 6.6) for Temperatures up to , Weather and Ultra-Violet Resistant for Indoor and Outdoor Applications, , Length of 284.4mm (11.10 Inches), Width of 3.56mm (0.14 Inches), , Tensile Strength Rating of 133.4 Newtons (30 pounds), Temperature up to 85 degress celsius (185 F)Bulk Pack
Product Type	Cable Tie 30LB 11.10IN Uv Black Nyl
Special Features	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time
Manufacturer Information	
Brand	Ty-Rap
GTIN	00786210839875
Manufacturers Part Number	TY26MX
UPC	786210839875



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## Taxonomies, Classifications, and Categories

Category Description	Screws, Bolts, Staples, Jack Chains, Washers & TY-Raps
Туре	HIGH PERFORMANCE
Availability	
minimum qty	1000
Packaging	
Carton	1000
Package	10000
Weight Per each	0.003
Uses, Certifications, and Standards	
standard	UL E49405 / UL E49405