

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 500 024 560 4685

We Deliver...Lower Cost, Quality Products, & Personal Service

Fax: 936-560-4685

ļ	ļ	ļ	
ļ	ļ	ļ	

U0653P 60A Acd NF 3PH 15HP Steel N3R

Industrial Conn & Sol

Catalog Number	U0653P
Manufacturer	Industrial Conn & Sol
Description	Metallic, Non-Fusible Disconnect Pullers Are Removable or
	Reinstallable In The Off Position For User Safety During
	Equipment Maintenance.
Weight per unit	8.5 (lbs/each)
Product Category	Non-Fusible Disconnect Safety

Features

amperage rating	60	
interrupt rating	10000	
Voltage Rating	240	

Dimensions and Weight

	-	
C' .	/ // 1 /	
Size	6 X 1/I	
JIZC	0 / 14	
	······································	

Descriptions

Description extra long description Long Description	60A ACD NF 3PH 15HP STEEL N3R MIDWEST U0653P MW 60A ACD NF 3PH 15 Metallic, Non-fusible disconnect pullers are removable or reinstallable in the OFF position for user safety during equipment maintenance.
Product Type	MW 60A Acd NF 3PH 15HP STL N3R
Special Features	Pullers are removable or reinstallable in the OFF position for user safety during equipment maintenance Door has padlock provisions to prevent unauthorized access Noryl thermoplastic enclosure is corrosion resistant and extremely durable, giving long maintenance free service Three-piece construction that opens up mounting and wiring areas, reduces installation time Numerous knockouts reduce installation time Straight-in, straight-out wiring saves time and money 265A6036G73 complete block and puller, 265A6

Manufacturer Information

Brand	MIDWEST	
GTIN	00784567561968	
Manufacturers Part Number	U0653P	
UPC	784567561968	

Taxonomies, Classifications, and Categories

Category Description	TEMP. POWER PANELS & ACCESSORIES
Туре	Non-Fused Pull-Out AC Disconnect Switch



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging		
Carton	1	
Weight Per each	8.5	
Uses, Certifications, and Standards		

Enclosure	Metallic	
Mounting	SURFACE	
standard	UL/cUL Listed	