



16100 South Lathrop Ave
Harvey, IL 60426

OFFICE / 708-339-1610
TOLL-FREE / 800-882-5543
WEB / atkore.com

September 5, 2018

AFC LIQUID-TUFF™ FLEXIBLE CONDUIT SAFETY DATA SHEET (SDS) & CALIFORNIA PROP 65

To Whom It May Concern:

Safety Data Sheets (SDS) are not provided for the attached list of products because these products are considered to be an “article” under the OSHA Hazard Communication Standard (HSC), 29 CFR 1910.1200.

This standard has an exemption for articles. To be considered as an article, the product has to be a manufactured item meeting the following criteria:

- During manufacture, the article must be formed to a specific shape or design
- The end-use functions are dependent in whole or in part on its shape or design and
- The product does not release or result in exposure to a hazardous chemical under normal conditions of use.

Products covered by this letter are not considered to be or to contain hazardous chemicals based on evaluations made by our company under the OSHA Hazard Communication Standard, 29 CFR 1910.1200. However, if your intent is to further process the product, please contact us so we can address that issue.

For more information, please refer to the following website:

<https://www.osha.gov/Publications/OSHA3514.html>

Atkore has also reviewed its compliance obligations under California’s updated Proposition 65 Clear & Reasonable Warning Regulations and has concluded that foreseeable use of the attached list of products do not result in exposures of listed chemicals requiring a warning.

Very truly yours,

Ruth Ensing

Ruth Ensing
Certification Specialist
Atkore International
Phone: 708-915-1543
Email: rensing@atkore.com



<i>PRODUCT FAMILY</i>	<i>DESCRIPTION</i>	<i>PRODUCT SERIES</i>
LFMC	Non UL Oil Resistant/High Temperature	5900
LFMC	Non UL Very Flexible	6100
Type LFMC	3/8, 1/2, 3/4, 1 1/2, 2, 2 1/2, 3, 3 1/2, 4 Liquid-Tuff Flexible Metal Conduit	6200
LFMC	CSA Hydrotite Com-Blue	6300
Type LFMC	1/2, 3/4, 1 1/2, 2, 2 1/2, 3 UL & CSA Computer Blue	6400
Type LFMC	3/8, 1/2, 3/4, 1 1/2, 2 UL & CSA Low Smoke Zero Halogen	6700
LFMC	3/8, 1/2, 3/4, 1 1/2, 2 Non UL Low Smoke Zero Halogen	6750
LFMC	Non UL Extreme Temperature	6800
Type LFMC	3/8, 1/2, 3/4, 2, 2 1/2, 3, 3 1/2, 4 UL Hi-Low Temperature	6900
LFMC	3/8, 1/2, 1 1/2, 2 UL & CSA NSF® 169 Component for Splash Zones	SZ00
LFMC	3/8, 1/2, 3/4, 1 1/2, 2, 2 1/2, 3, 4 CSA Hydrotite	HC00