



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



UNF75NRA 3/4" Alu Union *Appleton/Oz Gedney*

Catalog Number	UNF75NRA
Manufacturer	Appleton/Oz Gedney
Description	Unilets Unf Union, Trade Size: 3/4 In, Outside Diameter: 1-3/4 In, Length: 1.47 In, Flexibility: Rigid and Imc, Material: Copperfree (4/10 Of 1 PCT Maximum) Aluminum, Connection: Female Threaded, Finish: Natural, Standard: UI 886 (1203)
Weight per unit	0.1600 (lbs/each)
Product Category	Aluminum

Features

connection	Female Threaded
outside diameter	1-3/4

Dimensions and Weight

Length	1.47
--------	------

Descriptions

Description	3/4" ALU UNION
extra long description	APP UNF75NR-A 3/4 UNION CONNECTOR T
Long Description	UNILETS UNF Union, Trade Size: 3/4 IN, Outside Diameter: 1-3/4 IN, Length: 1.47 IN, Flexibility: Rigid And IMC, Material: Copperfree (4/10 Of 1 PCT Maximum) Aluminum, Connection: Female Threaded, Finish: Natural, Standard: UL 886 (1203)
Product Type	3/4 Union Connector Type Unf
Special Features	Accurately tapped, tapered threads for tight, rigid joints and ground continuity;Concentric ring interlocked design sizes makes possible smaller diameter, allowing use in tighter spaces;Explosionproof, dust-ignitionproof;Smooth, rounded integral bushing in each hub protects conductor insulation;UNF unions are used for joining conduit and connecting conduit to enclosures, Facilitates modifications, permits removal of enclosures without turning or removal of conduit

Manufacturer Information

Brand	Appleton
GTIN	00781381234139
Manufacturers Part Number	UNF75NR-A
UPC	781381234139

Taxonomies, Classifications, and Categories

Category Description	HAZARDOUS LOCATION FITTINGS
Type	UNF Union



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Trade Size

Trade Size 3/4

Packaging

Carton 10

Package 50

Weight Per each 0.16

Uses, Certifications, and Standards

Application For Connecting Conduit To Conduit
standard and Class III, CSA C22.2 No. 25, C22.2 No. 30, CSA 065181
..... Certified; Class II, Groups E, F, G; UL 886 (1203), UL File Number
..... E10444, UL Listed for Class I, Groups A, B, C, d