



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



UNL125 1/2" Male to 3/4" Female 90D Ell=Bow *Crouse-Hinds*

Catalog Number	UNL125
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Unl Union, Rigid/Imc, Gender End 1: Female, Gender End 2: Male, Feraloy Iron Alloy, 3/4" Female to 1/2" Male
Weight per unit	0.6800 (lbs/each)
Product Category	Rigid Conduit Fittings - Steel

Features

connection	Threaded
dimensions	2.6900 IN X 1.8100 IN X 2.0000 IN

Descriptions

Description	1/2" MALE TO 3/4" FEMALE 90D ELL=BOW
extra long description	CRS-H UNL125 3/4 NPT FEM TO 1/2 NPT
Features	Crouse-Hinds series explosionproof unions are installed in rigid/IMC conduit systems to connect conduit to conduit, a conduit fitting, junction box or device enclosure. Expansion unions are also available, which allow for expansion and contraction of conduit and compensate for conduit cut too short. Available in a variety of materials, including stainless steel, to suit customer preferences. Explosionproof elbows allow for a 90° change in direction to the conduit run, or when terminating at a box or fit
Long Description	Eaton Crouse-Hinds series UNL union, Rigid/IMC, Gender end 1: female, Gender end 2: male, Feraloy iron alloy, 3/4" female to 1/2" male
Product Type	3/4 NPT Fem to 1/2 NPT Male 90 Deg Union
Special Features	2-11/16 In Length X 1-13/16 In Width

Manufacturer Information

Brand	Eaton
GTIN	00782274806327
Manufacturers Part Number	UNL125
UPC	782274806327

Taxonomies, Classifications, and Categories

Category Description	HAZARDOUS LOCATION FITTINGS
Type	Union



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

Carton	1
Package	10
Weight Per each	0.68

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other
Enclosure	Condulet
standard	UL 886, CSA C22.2