

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Type

UNY125NR 1-1/4" Fem/Male Union

Appleton/Oz Gedney

Catalog Number	UNY125NR
Manufacturer	Appleton/Oz Gedney
Description	Unilets Uny Union, Trade Size: 1-1/4 In, Outside Diameter: 2.81 In, Length: 3.13 In, Flexibility: Rigid and Imc, Material: Malleable Iron, Connection: Male Threaded X Female Threaded, Finish: Triple-Coat (Zinc Electroplate, Chromate and
Weight per unit	1.7 (lbs/each)
Product Category	Rigid Conduit Fittings - Steel
eatures	
connection	Male Threaded X Female Threaded
outside diameter	2.81
imensions and Weight	
Length	3.13
escriptions	
Description	1-1/4" FEM/MALE UNION
extra long description	APP UNY125NR 1-1/4 UNION CONN TYPE
Long Description	UNILETS UNY Union, Trade Size: 1-1/4 IN, Outside Diameter: 2.8 IN, Length: 3.13 IN, Flexibility: Rigid And IMC, Material: Malleab Iron, Connection: Male Threaded X Female Threaded, Finish: Triple-Coat (Zinc Electroplate, Chromate And
Product Type	1-1/4 Union Conn Type Uny
Special Features	Accurately tapped, tapered threads for tight, rigid joints and ground continuity; Concentric ring interlocked design sizes make possible smaller diameter, allowing use in tighter spaces; Explosionproof, dust-ignitionproof; Smooth, rounded integral bushing in each hub protects conductor insulation; UNY unions are used for joining conduit and connecting conduit to enclosures, Facilitates modifications, permits removal of enclosures without turning or removal of conduit; With removable male nipple
lanufacturer Information	
Brand	Appleton
GTIN	
Manufacturers Part Number	UNY125NR
UPC	781381257725

Category Description HAZARDOUS LOCATION FITTINGS

UNY Union



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Trade Size Trade Size	1-1/4
Packaging Carton	5
Package	25
Weight Per each	1.66
Uses, Certifications, and Stand	dards
Application	For Connecting Conduit To Enclosure
standard	and Class II, CSA C22.2 No. 25, C22.2 No. 30, CSA 065181
	Certified; Class II, Groups E, F, G; UL 886 (1203), UL File Number
	E10444, UL Listed for Class I, Groups B, C, d