



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## **USE10STBK500 Cu Use #10 STR Black 500'** *Southwire Company*

Catalog Number	USE10STBK500
Manufacturer	Southwire Company
Description	Service Entrance Cable, Conductors Shall Be Annealed Copper, Cross-Linked Polyethylene (XLP) Insulated, As Manufactured By Southwire Company or Approved Equal Additional Information, Underground Service Entrance Application, Black, Copper Conductor Material, 320 A (60°C);380 A (75°C);430 A (90°C) Current Rating, Cross-Linked Polyethylene Insulation Material, 95 Mil Insulation Thickness, Made In Usa, +90 °C Maximum Operating Temperature, 37 - Strands, 983 Mil Outside Diameter, 1000 FT Overall Length, Reel P
Weight per unit	0.0490 (lbs/ft)
Product Category	Use RHH-RHW-STR (Stranded)

### **Features**

Conductor Size	10
Number of Conductors	1

### **Dimensions and Weight**

Length	500
--------	-----

### **Descriptions**

Description	CU USE #10 STR BLACK 500'
extra long description	SWC 11344903 USE 10 Str Cu Bk 500Sp

### **Manufacturer Information**

Brand	Copper
GTIN	00032886276019
Manufacturers Part Number	11344903
UPC	032886276019

### **Taxonomies, Classifications, and Categories**

Category Description	BUILDING WIRE
Type	USE-2

### **Packaging**

Carton	500
Weight Per foot	0.049