

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Width

#### **VW150IM12 150W WL MNT V/T Fix**

Lithonia Lighting - Acuity

Catalog Number	VW150IM12
Manufacturer	Lithonia Lighting - Acuity
Description	Utility Wall-Mounted Fixture For Entrances, Hallways, Closets
	Tunnels, or Other Utility Applications
Weight per unit	2.5 (lbs/each)
Product Category	Incandescent Vapor Tight Light
eatures	
average life	Not Applicable
Ballast Type	Not Applicable
dimensions	Not Applicable
Hardware	Yes
Lamp Included	NO
Lamp Type	Incandescent
Material	Aluminum
Number of Lamps	1
pallet quantity	192
Power Source	Hardwired
Shape	Round
Socket Type	Medium: Screw
Voltage Rating	120
Warranty	2
Wattage	150
Material, Color, and Finish	
Color	Gray
Finish	Gloss
fixture material	aluminum
Lens Material	Glass
Style	Traditional
Dimensions and Weight	
Height	10.0000
Length	7.2500

7.2500



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

_	•		
11000	rın	tia	nc
Desc	,		· ·

Description	150W WL MNT V/T FIX
extra long description	LITH VW150I M12 Utility vapor tight
Long Description	Utility wall-mounted fixture for entrances, hallways, closets, tunnels, or other utility applications
Product Type	Wallpack
Special Features	Utility wall-, ceiling- or pendant-mounted fixtures for entrances, hallways, closets, tunnels or other utility applications. Incandescent, fluorescent, metal halide or high pressure sodium sources are available.

#### **Manufacturer Information**

Brand	Lithonia Lighting	
GTIN	00745973817681	
Manufacturers Part Number	VW150I M12	
UPC	745973817681	

### Taxonomies, Classifications, and Categories

Packaging		
Carton	1	
Weight	2.0000	

2.5

Hazardous Industrial

### Uses, Certifications, and Standards

Weight Per each

Application	Education, Hospitality, Offices & Banks
environmental conditions	OUTDOOR
standard	cUL