



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



WH5 NPT-1-1/2 WP Conduit Hub *Hubbell--Killark*

| | |
|------------------|---------------------------------------|
| Catalog Number | WH5 |
| Manufacturer | Hubbell--Killark |
| Description | 1-1/2" Zinc Weather Proof Conduit Hub |
| Weight per unit | 0.7200 (lbs/each) |
| Product Category | Liquid Tight Fittings |

Material, Color, and Finish

| | |
|--------|-----------|
| Color | Gray |
| Finish | Untreated |

Dimensions and Weight

| | |
|----------|--------|
| Height | 1.92 |
| Hub Size | 1-1/2" |
| Length | 2.745 |
| Width | 2.745 |

Descriptions

| | |
|------------------------|---|
| Description | NPT-1-1/2 WP CONDUIT HUB |
| extra long description | KLRK WH-5 WEATHERPROOF CONDUIT HUB |
| Long Description | 1-1/2" Zinc Weather Proof Conduit Hub |
| Product Type | Weatherproof Conduit Hub 1 1/2 |
| Special Features | Oversized locknut provides for a strong vibration-proof termination. Captive sealing ring. Serrations on hub body and locknut provide effective positive ground path. Rugged cast zinc construction. Insulated throat protects conductors. Suitable for use wit |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | KILLARK |
| GTIN | 00783936841847 |
| Manufacturers Part Number | WH-5 |
| series | WH |
| UPC | 783936841847 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|-------------------------------------|
| Category Description | FORM 5 CONDULETS, COVERS, & GASKETS |
| Type | Weatherproof Conduit Hub |

Packaging

| | |
|-----------------|------|
| Carton | 1 |
| Package | 20 |
| Weight Per each | 0.72 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Uses, Certifications, and Standards

Application

Conduit hubs provide a liquid tight, oil tight and dust tight termination of electrical conduit through the walls of sheet metal enclosures. The hubs fit into standard knock-out dimensions.

standard

UL, CSA