



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



WLQT Wire Pulling Lubricant Gel, 1 Quart *Minnesota Mining (3M)*

Catalog Number	WLQT
Manufacturer	Minnesota Mining (3M)
Description	3M™ Wire Pulling Lubricant WL Is A Translucent Polymer Gel That Acts As An Excellent Lubricant For Pulling Both Electrical and Communication Cable. This Lubricant Gel Wipes Off The Cable Quickly and Cleanly Before Terminating or Splicing. The Lubricant Has A Low Coefficient Of Friction Which Lessens The Chance Of Cable Jacket Damage From High Pulling Forces.
Weight per unit	0.1947 (lbs/each)
Product Category	Paint, Chemicals, Etc.

Descriptions

Description	WIRE PULLING LUBRICANT GEL, 1 QUART
extra long description	3M 7000058273 3M™ Wire-Pulling Lubr
Features	3M™ Wire Pulling Lubricant WL is a consistent gel that does not liquefy, or separate with hot or cold aging. It stays thick, smooth and ready to apply. Temperature range of 20 to 110 degrees F (-6.7 to 43 degrees C).
Long Description	3M™ Wire Pulling Lubricant WL is a translucent polymer gel that acts as an excellent lubricant for pulling both electrical and communication cable. This lubricant gel wipes off the cable quickly and cleanly before terminating or splicing. The lubricant has a low coefficient of friction which lessens the chance of cable jacket damage from high pulling forces.
Product Type	3M™ Wire-Pulling Lubricant WL
Special Features	Translucent White

Manufacturer Information

Brand	3M
GTIN	00054007506225
Manufacturers Part Number	WL-QT
UPC	054007506225

Taxonomies, Classifications, and Categories

Category Description	ADHESIVES
Type	Gel

Packaging

Carton	12
Weight Per each	0.1947

Uses, Certifications, and Standards

Application	Lubricant
-------------	-----------