On-Q

# Category 5e RJ45 Keystone Connector, White

Part No. WP3450WH




Optimize your network setup with this Category 5e RJ45 Keystone Connector in white. The vertical design makes punchdown termination simple, while the rear retention caps ensure secure wire connections. This insert is compatible with all Keystone wall plates and meets Category 5e performance standards for reliable network performance.

## Features & Benefits

- Ensures Category 6 performance standard compliance
- Vertical design for easy punchdown termination
- Meets Category 5e described in TIA/EIA-568-B.2
- Jack housing is high-impact, flame resistant plastic, UL 94V-0
- Also available in contractor pack of 50 (WP3450-WH-50)
- Rear retention caps ensure secure wire termination
- T568A and T568B wiring labels included
- Insertion and extraction life is 750 Cycles Min
- Spring wire is phosphor bronze alloy plated with 50 micro-inch of gold over 100 micro-inches of nickel

## Specifications

### General Info

| | | | |
|---|---|---|---|
| Product Line | On-Q | Color | White |
| UPC Number | 804428024873 | Country Of Origin | Taiwan, Province Of China |
| Application Sector | Residential | Standard | CSA, cULus, RoHS, ANSI/UL 1863, Flame-Retardant Plastic UL 94V-0 |

### Dimensions

| | | | |
|---|---|---|---|
| Product Width US | 0.64 in | Product Height US | 0.87 in |
| Product Length US | 1.28 in | | |

## Technical Information

| | | | |
|---|---|---|---|
| Termination Style | Punchdown | Cable Type | Cat5e |
| Environmental Conditions | 0 to 93% (relative humidity, non-condensing) | | |

On-Q

# Category 5e RJ45 Keystone Connector, White

Part No. WP3450WH




Optimize your network setup with this Category 5e RJ45 Keystone Connector in white. The vertical design makes punchdown termination simple, while the rear retention caps ensure secure wire connections. This insert is compatible with all Keystone wall plates and meets Category 5e performance standards for reliable network performance.

## Features & Benefits

- Ensures Category 6 performance standard compliance
- Vertical design for easy punchdown termination
- Meets Category 5e described in TIA/EIA-568-B.2
- Jack housing is high-impact, flame resistant plastic, UL 94V-0
- Also available in contractor pack of 50 (WP3450-WH-50)
- Rear retention caps ensure secure wire termination
- T568A and T568B wiring labels included
- Insertion and extraction life is 750 Cycles Min
- Spring wire is phosphor bronze alloy plated with 50 micro-inch of gold over 100 micro-inches of nickel

## Specifications

### General Info

| | | | |
|---|---|---|---|
| Product Line | On-Q | Color | White |
| UPC Number | 804428024873 | Country Of Origin | Taiwan, Province Of China |
| Application Sector | Residential | Standard | CSA, cULus, RoHS, ANSI/UL 1863, Flame-Retardant Plastic UL 94V-0 |

### Dimensions

| | | | |
|---|---|---|---|
| Product Width US | 0.64 in | Product Height US | 0.87 in |
| Product Length US | 1.28 in | | |

## Technical Information

| | | | |
|---|---|---|---|
| Termination Style | Punchdown | Cable Type | Cat5e |
| Environmental Conditions | 0 to 93% (relative humidity, non-condensing) | | |