

## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Catalog Number	WR20TRW
Manufacturer	Pass & Seymour/Legrand
Description	Tamper-Resistant, Weather-Resistant Commercial Grade Receptacles, 20A, 125V
Weight per unit	0.2005 (lbs/each)
Product Category	
atures	
amperage rating	20
connection	Sido wiro
Dielectric Strength	Withstands 1500V minimum
indoor/outdoor	
Number of Wires	
Outlet Type	Weather-Resistant, Tamper-Resistant
Poles	
Voltage	125.0 V
Voltage Rating	125
Wattage	Electrical power is expressed in Amps and Volts.
Wire Size	14 - 10
aterial, Color, and Finish	
Finish	Matte
mensions and Weight	
Height	3.281
Width	1.130
escriptions	
Description	WR DUPLEX RECP TR 20A/125V WH
extra long description	
Long Description	Tamper-Resistant, Weather-Resistant Commercial Grade
Product Type	
Special Features	Auto-ground clip assures positive ground. WR marking on face
Special reatures	required by UL Standard. Zinc-plated steel mounting screws for greater ease of installation and removal in wet or damp locations. Strap tabs wrap around face to prevent strap from separating from face and back body. Tri-drive brass terminal screws. Side wire capability. Heavy-duty, brass strap for added strength and ground conductivity. UV-resistant nylon face for

screws anchor stra

longer life under adverse environmental conditions. Two drive



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## Manufacturer Information

Brand	LEGRAND-PASS & SEYMOUR
GTIN	00785007242577
Manufacturers Part Number	WR20-TRW
UPC	785007242577
Taxonomies, Classifications, and Cate	gories
	Residential Switches
Туре	Outlet
Trade Size	
Amperage	15.0
Packaging	
Carton	
Package	100
Weight Per each	0.2005
Uses, Certifications, and Standards	
Application	Commercial
environmental conditions	Flammability: UL94 V2
Mounting	WALL
nema rating	5-20R
standard	CULUS, UL498, CSA C22.2 No. 42