

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



WR359 4/0 to 3 H Tap Conn Abb Installation Products, Inc

Catalog Number	WR359
Manufacturer	Abb Installation Products, Inc
Description	Aluminum Wide Range H-Type Compression Connector Main: 4/0 - 3/0 Acsr, 4/0 - 3/0 STR., Tap: 4-6 Acsr, 3-6 STR., 2-6 Sol., Die: D,
	D3. 1-7/8 Inch.
Weight per unit	0.1390 (lbs/each)
Product Category	Large Terminals & Connectors
Features	ç
connection	Compression
insulation	None
Material	Aluminum
Number of Conductors	2
Wire Size	Main: 4/0 to 3/0 ACSR or 4/0 to 3/0 STR AWG, Tap: #4 to #6
	ACSR or #3 to #6 STR or #2 to #6 SOL AWG
Material, Color, and Finish	
Housing Material	Aluminum
Dimensions and Weight	
Size	Length 1-7/8 inch
Descriptions	
Description	4/0 TO 3 H TAP CONN
extra long description	ABB WR359 AL HTYPE COMP CONN 4/0-3/
Long Description	Aluminum Wide Range H-Type Compression Connector Main: 4/0 - 3/0 ACSR, 4/0 - 3/0 Str., Tap: 4-6 ACSR, 3-6 Str., 2-6 Sol., Die: D, D3. 1-7/8 inch.
Product Type	AI Htype Comp Conn 4/0-3/0ASCR 4-6
Special Features	Made of 1350 Aluminum Alloy for high strength and high
	conductivity. Standard Compression tools and dies install all
	sizes - no special tools needed. Field-proven ribbed design
	enables excellent connector/conductor contact without
	distorting the conductor's shape. Fold-in tabs provide tab
	interlock as tool closes. Prefilled with oxide inhibitor held captive
	in the rib/connection area
Manufacturer Information	
Brand	Blackburn Mechanical
GTIN	00783786100088
Manufacturers Part Number	WR359
UPC	783786100088



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	T&B C TAP LUGS
Туре	H-Type Compression Tap Connector
Packaging	
Carton	25
Package	250
Weight Per each	0.139
Uses, Certifications, and Standard	ds
Application	For Combinations of Aluminum to Aluminum and Aluminum to Copper Conductors
environmental conditions	All Seasons / Conditions
Mounting	None
standard	RUS Accepted. Complies with ANSI C119.4 Specifications
Temperature Rating	up to 90 C