ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



# WT51B Wingtwist Wire Connector, WT51 Yellow, 500/Bag

*Ideal*

| | |
|---|---|
| Catalog Number | WT51B |
| Manufacturer | Ideal |
| Description | Wing Twist Connector, (2) #18 Awg Conductor Size, (3) #12 Awg Conductor Size, Yellow Insulation Color, +221 °F Operating Temperature, 1 to 6 Conductors, 600 V Ac, 2.1 LB |
| Weight per unit | 2.1 (lbs/each) |
| Product Category | Electrical Fixture Conn ( Nuts |

## Features

| | |
|---|---|
| Material | Flame-retardant Polypropelene |
| Voltage Rating | 600 |

## Material, Color, and Finish

| | |
|---|---|
| Color | Yellow |

## Descriptions

| | |
|---|---|
| Description | WINGTWIST WIRE CONNECTOR, WT51 YELLOW, 500/BAG |
| extra long description | IDEAL WT51-B WINGTWIST WT51 YELLOW, |
| Features | With a full line for virtually every wire size and combination, the WingTwist Wire Connector offers a great combination of performance and value.The contoured wing design of the WingTwist provides maximum torque for a variety of electrical applications while the copolymer shell and live-action spring expand for smooth, progressive tightening providing dependable connections.With a tough, flame-retardant shell that withstands environmental extremes, and a long, deep skirt to provide maximum dielectric prote |

## Manufacturer Information

| | |
|---|---|
| Brand | Buchanan |
| GTIN | 00781789611013 |
| UPC | 781789611013 |

## Taxonomies, Classifications, and Categories

| | |
|---|---|
| Category Description | WIRE NUTS |

## Availability

| | |
|---|---|
| minimum qty | 500 |

## Packaging

| | |
|---|---|
| Carton | 500 |
| Package | 5000 |
| Weight Per each | 2.1 |

ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

## Uses, Certifications, and Standards

| | |
|---|---|
| Application | Insulating or Joining 1 or more conductors |
| environmental conditions | Tough, UL 94V-2 Flame-Retardant Shell Rated At 105 DEG C (221 F) |
| standard | CSA C22.2 #188, UL 486C Listed, RoHS |