

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



XHHW2500RPCS AI XHHW 250 STR Orange PCS King Wire Inc.

King wire inc.	
Catalog Number	XHHW2500RPCS
Manufacturer	King Wire Inc.
Description	Aluminum Building Wire, Abrasion, Moisture, Heat and Sunlight Resistant Insulation; Cable Can Be Installed Without Pulling Lubricant Additional Information, General Purpose Wiring Application, Orange Color, Aluminum Conductor Material, 250 MCM Conductor Size, 230 A Current Rating, Polyethylene Insulation Material, 65 Mil Insulation Thickness, Made In Usa, +90 °C Maximum Operating Temperature, 37 - Strands, 0.655 In Outside Diameter, 1000 FT Overall Length, Carton Package Type, Directive 2002/95/Ec;Federal S
Weight per unit	0.2930 (lbs/ft)
Product Category	XHHW-STR (Stranded)
Descriptions	
Description	AL XHHW 250 STR ORANGE PCS
Manufacturer Information	
Brand	Aluminum

Taxonomies, Classifications, and Categories **Category Description** ALUM BUILDING WIRE

Packaging

Carton	1
Weight Per foot	0.293