

Specifications



Eaton XTCEXFAC04

Eaton Contactor Accessory Auxiliary Contact, Four-pole, Screw terminals, 4NC contact configuration, 16A conventional thermal rating, 6A at 220/230/240V, 3A at 380/400/415V, 1.5A at 500V rated operational voltage, Front mounting,

General specifications

PRODUCT NAME	Eaton motor control auxiliary contact
CATALOG NUMBER	XTCEXFAC04
UPC	782116354559
PRODUCT LENGTH/DEPTH	1.5 in
PRODUCT HEIGHT	1.3 in
PRODUCT WIDTH	1.5 in
PRODUCT WEIGHT	0.12 lb
COMPLIANCES	CCC Marked CE Marked ATEX Compliant
CERTIFICATIONS	IEC 60947 EN 60947 UL Listed CSA Certified
CATALOG NOTES	Interlocked opposing contacts, to IEC/EN 60947-5-1 Annex L (positively driven), within the auxiliary contact modules (not NOE and NCL contacts) and between the auxiliary contacts and built-in contacts of the XTRE control relays.



Powering Business Worldwide

Product specifications

USED WITH	XTRE control relays
NUMBER OF POLES	Four-pole
TYPE	Contactors Accessory - Auxiliary Contact
TERMINALS	Screw
CONTACT CONFIGURATION	4 NC
MOUNTING METHOD	Front
RATED OPERATIONAL CURRENT	6A at 220/230/240V; 3A at 380/400/415V; 1.5A at 500V
SPECIAL FEATURES	Used with XTRE control relays
CONVENTIONAL THERMAL CURRENT	16A
QUANTITY	5

Resources

SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - XTCEXFAC04](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.



Specifications



Eaton XTCEXFAC04

Eaton Contactor Accessory Auxiliary Contact, Four-pole, Screw terminals, 4NC contact configuration, 16A conventional thermal rating, 6A at 220/230/240V, 3A at 380/400/415V, 1.5A at 500V rated operational voltage, Front mounting,

General specifications

PRODUCT NAME	Eaton motor control auxiliary contact
CATALOG NUMBER	XTCEXFAC04
UPC	782116354559
PRODUCT LENGTH/DEPTH	1.5 in
PRODUCT HEIGHT	1.3 in
PRODUCT WIDTH	1.5 in
PRODUCT WEIGHT	0.12 lb
COMPLIANCES	CCC Marked CE Marked ATEX Compliant
CERTIFICATIONS	IEC 60947 EN 60947 UL Listed CSA Certified
CATALOG NOTES	Interlocked opposing contacts, to IEC/EN 60947-5-1 Annex L (positively driven), within the auxiliary contact modules (not NOE and NCL contacts) and between the auxiliary contacts and built-in contacts of the XTRE control relays.



Powering Business Worldwide

Product specifications

USED WITH	XTRE control relays
NUMBER OF POLES	Four-pole
TYPE	Contactor Accessory - Auxiliary Contact
TERMINALS	Screw
CONTACT CONFIGURATION	4 NC
MOUNTING METHOD	Front
RATED OPERATIONAL CURRENT	6A at 220/230/240V; 3A at 380/400/415V; 1.5A at 500V
SPECIAL FEATURES	Used with XTRE control relays
CONVENTIONAL THERMAL CURRENT	16A
QUANTITY	5

Resources

SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - XTCEXFAC04](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

