

Eaton XTCEXFAC04

Catalog Number: XTCEXFAC04

Eaton Contactor Accessory Auxiliary Contact, Four-pole, Screw terminals, 4NC contact configuration, 16A conventional thermal rating, 6A at 220/230/240V, 3A at 380/400/415V, 1.5A at 500V rated operational voltage, Front mounting,



General specifications

Product Name

Eaton motor control auxiliary contact

Catalog Number

XTCEXFAC04

UPC

782116354559

Product Length/Depth

1.5 in

Product Height

1.3 in

Product Width

1.5 in

Product Weight

0.12 lb

Compliances

CCC Marked

CE Marked

ATEX Compliant

Certifications

IEC 60947

EN 60947

UL Listed

CSA Certified

Catalog Notes

Interlocked opposing contacts, to IEC/EN 60947-5-1 Annex L (positively driven), within the auxiliary contact modules (not NOE and NCL contacts) and between the auxiliary contacts and built-in contacts of the XTRE control relays.

Product specifications

Used with

XTRE control relays

Number Of Poles

Four-pole

Type

Contactory Accessory - Auxiliary Contact

Terminals

Screw

Contact configuration

4 NC

Mounting method

Front

Rated operational current

6A at 220/230/240V; 3A at 380/400/415V; 1.5A at 500V

Special features

Used with XTRE control relays

Conventional thermal current

16A

Quantity

5

Resources

Specifications and datasheets

[Eaton Specification Sheet - XTCEXFAC04](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia

Eaton XTCEXFAC04

Catalog Number: XTCEXFAC04

Eaton Contactor Accessory Auxiliary Contact, Four-pole, Screw terminals, 4NC contact configuration, 16A conventional thermal rating, 6A at 220/230/240V, 3A at 380/400/415V, 1.5A at 500V rated operational voltage, Front mounting,



General specifications

Product Name

Eaton motor control auxiliary contact

Catalog Number

XTCEXFAC04

UPC

782116354559

Product Length/Depth

1.5 in

Product Height

1.3 in

Product Width

1.5 in

Product Weight

0.12 lb

Compliances

CCC Marked

CE Marked

ATEX Compliant

Certifications

IEC 60947

EN 60947

UL Listed

CSA Certified

Catalog Notes

Interlocked opposing contacts, to IEC/EN 60947-5-1 Annex L (positively driven), within the auxiliary contact modules (not NOE and NCL contacts) and between the auxiliary contacts and built-in contacts of the XTRE control relays.

Product specifications

Used with

XTRE control relays

Number Of Poles

Four-pole

Type

Contactory Accessory - Auxiliary Contact

Terminals

Screw

Contact configuration

4 NC

Mounting method

Front

Rated operational current

6A at 220/230/240V; 3A at 380/400/415V; 1.5A at 500V

Special features

Used with XTRE control relays

Conventional thermal current

16A

Quantity

5

Resources

Specifications and datasheets

[Eaton Specification Sheet - XTCEXFAC04](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)